

Technical Sheet

Dishwashing Flight Conveyor

Mod. C-5010-T ECO

Jemi Simply
built to last

Professional Dishwashing
and Cooking Equipment

Selva de Mar, 122-128
08020 Barcelona, España
Tel. 0034 93 308 31 54
Fax. 0034 93 303 38 73
jemi@jemi.es
www.jemi.es



Characteristics

| | |
|--------------------------------|-------------------------------|
| Dimensions | 5010 x 830 x 1715 mm |
| Speeds | 2 |
| Production Racks / Dishes hour | 2200 - 3400 |
| Usable washing height | 380 mm |
| Water Consumption hour | 280 l/h |
| Water connexion | 3/4" |
| Water inlet pressure | 2 - 4 bars / 200 - 400 Kpa |
| Drainage | ø 50 mm |
| N° Upper prewashing arms | 3 |
| N° Lower prewashing arms | 3 |
| N° Upper washing arms | 3 |
| N° Lower washing arms | 3 |
| Prewash / Wash tank capacity | 50 L |
| ECO-Rinse tank capacity | 20 L |
| Boiler capacity | 11,5 L |
| Prewash pump power | 2 kw |
| Washing pump power | 2 kw |
| ECO-Rinse pump power | 0,074 kw |
| Tank heating element | 18 kw |
| Boiler heating element | 24 kw |
| ECO-Rinse heating element | 6 kw |
| Drying heating element | 6 kw |
| Total Power | 59 Kw (47 Kw*) |
| Voltage | 230 - 400V / III / 50 - 60 Hz |

Modules

| | |
|------------------------------------|---|
| Entrance 720 mm | ● |
| Prewash + Post prewash rinse | ● |
| Wash | ● |
| Double Rinse | ● |
| Enhanced ECO-Rinse | ● |
| Drying | ● |
| Useful Exit 1150 mm | ● |

* In case of hot water supply, possibility of reducing power by commuting elements.

